

Burden Statement

A federal agency may not conduct or sponsor, and a person is not required to respond to, nor shall a person be subject to a penalty for failure to comply with a collection of information subject to the requirements of the Paperwork Reduction Act unless that collection of information displays a current valid OMB Control Number. The OMB Control Number for this information collection is 2138-0046 (Exp. Date 03/31/2017). Reporting of an Equipment Failure is estimated to take approximately 30 minutes, including the time for reviewing instructions, completing and reviewing the report. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to: SafeOCS Data Collection Office, Demetra Colliia, US DOT/ BTS, 1200 New Jersey Avenue SE, Room E36-302, Washington, D.C. 20590 or e-mail: Demetra.colliia@dot.gov

Pledge of Confidentiality

The information you provide will be used for statistical purposes only. In accordance with the BTS confidentiality statute (49 U.S.C. 6307) and the Confidential Information Protection provisions of Title V, Subtitle A, Public Law 107-347, your responses will be kept confidential and will not be disclosed in identifiable form to anyone other than BTS employees or BTS agents such as telephone interviewers. In accordance with these confidentiality statutes, only statistical and non-identifying data will be made publicly available through aggregate reports. By law, every BTS employee and BTS agent has taken an oath of confidentiality and is subject to a jail term of up to 5 years, a fine of up to \$250,000, or both if he or she discloses ANY identifiable information about the respondent or reporting company or operator. BTS will not release to the Bureau of Safety and Environmental Enforcement, Department of Interior, or any other public or private entity any information that might reveal the identity of individuals or company/operator names mentioned in near-miss reports.

SPPE (Safety and Pollution Prevention Equipment) Failure Notification Form
(Please submit the information listed below)

I. Operator Data

Date of Failure _____

Operator Company Name _____

(Operators will select their BSEE operator number from a drop down list that BSEE will provide)

Complex ID / Structure Number _____/_____

(Operators will select their Complex ID and Structure Number from a drop down list that BSEE will provide)

API Well Number, if applicable _____

Company Name Submitting Form, if different than the Operator _____

Type of Company Submitting Form (select one)

- Production Contractor
- Other, Specify _____

II. SPPE Details

Equipment manufacturer _____

Model _____

Serial Number _____

Working pressure _____

Nominal size _____

Provide a narrative describing any redress history for the SPPE that failed:

Please provide the date and a narrative description of the last SPPE test.

Date _____

Narrative:

III. What was the Certification Status of the Failed SPPE (*select one*)

- Newly Installed; certified SPPE pursuant to ANSI/API Spec Q1
 - Newly Installed; certified SPPE pursuant to Another Quality Assurance Program
 - Previously certified under ANSI/ASME SPPE-1
 - Non-Certified SPPE
-

IV. Was the SPPE previously repaired, remanufactured or subject to hot work offsite? Yes No

V. What type of tree was associated with the SPPE that failed? (*select one*)

- Dry Tree
 - Subsea Tree
-

VI. Which SPPE component failed? (*select all that apply*)

- Valve Body
 - Actuator
 - Flow coupling (required for surface- or subsurface-controlled SSSV)
 - Safety Lock
 - Landing Nipple
 - Direct hydraulic control system
 - Electro-hydraulic control umbilical
 - Flange
 - Ring joints
 - Ball
 - Flapper
 - Temperature Safety Element (TSE)
 - Emergency Shutdown (ESD) System
-

VII. SPPE Type

What was the type of SPPE that failed? (*select one*)

- Surface Safety Valve (SSV)
 - Boarding Shutdown Valve (BSDV)
 - Underwater Safety Valve (USV)
 - Surface controlled SCSSV
 - Subsurface controlled SSCSV
-

VIII. SSSV Details

What was the type of SSSV that failed? (*select one*)

- Tubing retrievable

- Wireline retrievable
- Through flowline (TFL)
- SSCSV retrievable
- SSCSV retrievable

Was the SSSV formerly a pump through type tubing plug? Yes No

If the SSSV that failed was Subsurface Controlled (SSCSV), what type was it? *(select one)*

- Velocity-type SSCSV
- Tubing-pressure-type SSCSV

What was the service class of the SSSV that failed? *(select one)*

- Class 1 only standard service
- Class 2 sandy service
- Class 1 and 2
- Class 3 stress cracking
- Class 3s (sulfide stress and chlorides in a sour environment)
- Class 3c (sulfide stress and chlorides in a non-sour environment)
- Class 4 mass loss corrosion service

X. BDSVs, SSVs, and USVs

What was the service class of the BDSV/SSV/USV? *(select one)*

Class I: performance level requirement intended for use on wells that do not exhibit the detrimental effects of sand erosion.

Class II: performance requirement level intended of use if a substance such as sand could be expected to cause an SSV/USV valve failure

If the SPPE that failed was a BSDV, which type was it? *(select one)*

- Automatic
- Manual BSDV

X. SPPE Design Criteria

Was the SPPE designed for High Pressure High Temperature (HPHT) conditions? Yes No

Was the SPPE designed for Arctic Conditions? Yes No

Please specify the most extreme exposure conditions for which the SPPE was designed to function?

Design Pressure _____ psi

Design Temperature _____ degrees F

Design Flow Rate _____ (number) Flow rate units _____ per _____

Other Design Environmental Conditions _____

XI. Well data (Provide the information below, as applicable)

What was the type of well associated with the SPPE failure? (select one)

- Production
- Injection Well

Was the well shut in at the time of failure? Yes No

What was the last Well Test Rate? _____ BOE/day

What was the date of the last Well Test? _____

What were the Environmental Conditions (check all that apply)

- Sand, Specify percentage _____%
- H2S
- CO2
- Other, Specify _____

Pressures and temperatures

Surface _____ psi / _____ degrees F

Bottom hole _____ psi / _____ degrees F

XII. Under what conditions was the SPPE activated at the time of the failure (check all that apply)

- Activated during normal well operations
- Activated in response to an ESD
- Activated during emergency weather or other emergency conditions
Specify the nature of the emergency: _____
- Activated during a process upset
- Activated in response to the detection of a high or a low pressure condition by a PSHL sensor located upstream of the BSDV
- Activated when the gas lift system introduced gas into the system
- Activated during a leakage test

XIII. Description of the failure

Provide a narrative description of the failure to include, **but not limited to:**

- as much information as possible on the operating conditions that existed at the time of the malfunction or failure
- an accurate a description as possible of the malfunction or failure

- any operating history of the SPPE leading up to the malfunction or failure (e.g. field repair, modifications made to the SPPE, etc.)

XIV. Specify how many cycles or hours were completed since the last preventative maintenance.
(If the SPPE was newly installed, specify how many cycles or hours were completed since the SPPE was installed).

_____ number of cycles or _____ number of hours

XV. Provide a narrative describing the general configuration of the SPPE and hydrocarbon flow path.

XVI. What factors contributed to the failure? (select all that apply)

- Improper Design
- SPPE erroneously thought to be certified but was not
- Inadequate requalification/verification testing
- Installation was incompatible with specific design elements like subsea trees and related equipment, tubing hangers, etc.
- Improper Use
- Operating conditions out of range of device
- Mechanical failure – leak
- Mechanical failure -- sand cut erosion
- Mechanical failure – Corrosion (chemical - H2S or CO2)
- Mechanical failure -- Corrosion (atmosphere)
- Valve seat degradation
- Failed to open
- Failed to close
- Failed to contain hydrocarbons
- Failure to meet required closure timing (consider both isolation and bleed time when deciding)
- Electrical power failure

- Hydraulic power failure
- Incorrect assembly
- Valve damaged during assembly/disassembly
- Improper maintenance
- Improper repair
- Shipping damage
- Damage related to lifting or material handling
- Storm damage
- Collision damage
- Damage related to a seismic event
- Applied hydraulic pressure through wellhead seal assembly required to maintain surface-controlled SSSV in the open position exceeds MRWP of the wellhead by more than a minimum required amount
- Other, Specify _____

XVII.Preliminary Root Cause (select all that apply)

- Human Error, Personnel Skills or Knowledge
- Human Error, Quality of Task Planning and Preparation
- Human Error, individual or group decision-making
- Human Error, quality of task execution
- Human Error, quality of hazard mitigation
- Human Error, communication
- Maintenance plan and procedure
- Manufacturing defect
- Design issue
- Wear and tear
- Other, Specify _____

XVIII.Is a formal Root Cause and Failure Analysis recommended? Yes No

XIX.Corrective Action

What corrective action was taken related to the SPPE failure? (select all that apply)

- Adjust
- Check
- Inspection
- Modify
- Overhaul
- Refit
- Remanufacturer
- Repair

- Replace
- Service
- Test
- Other, Specify _____

Where was the corrective action accomplished? *(select one)*

- Contractor's facility
- Manufacturer's facility
- On location
- Operator's facility

If the corrective action was accomplished on location, who conducted the corrective action?
(select one)

- Operator
- Contractor
- Manufacturer

XX. Was the failure associated with an HSE Incident: Yes No

If Yes, what was the type of incident? *(select all that apply)*

- One or More Fatalities
- Injury to 5 or more persons in a single incident
- Tier 1 Process Safety Event (API 754/IOGP 456)
- Loss of Well Control
- \$1 million direct cost from damage of loss of facility/vessel/equipment
- Oil in the water >= 10,000 gallons (238 bbls)
- Tier 2 Process safety event (API 754/IOGP 456)
- Collisions that result in property or equipment damage > \$25,000
- Incident involving crane or personnel/material handling operations
- Loss of Station-keeping
- Gas release (H2S and Other) that result in process or equipment shutdown
- Muster for evacuation
- Structural Damage
- Spill < 10,000 gallons (238 bbls)
- Other, Specify _____

Appendix

List of Acronyms and References	
The Act	Outer Continental Shelf Lands Act
AIV	alternate isolation valve
ANSI	American National Standards Institute
API	American Petroleum Institute
APM	Application for Permit to Modify
ASME	American Society of Mechanical Engineers
BAST	Best available and safest technology
BOEM	Bureau of Ocean Energy Management
BOPs	Blowout Preventers
BSDV	Boarding shutdown valves
BSEE	Bureau of Safety and Environmental Enforcement
CSU	column-stabilized-unit
CVA	certified verification agent
DOI	Department of the Interior
DPP	Development and Production Plan
DWOP	Deepwater Operations Plan
E.O.	Executive Order
ESD	emergency shutdown
FPS	floating production systems
FPSO	floating production, storage, and offloading facility
FSV	flow safety valves
GLIV	gas-lift isolation valve
GOM	Gulf of Mexico
H ₂ S	hydrogen sulfide
HP	high pressure
HPHT	high pressure high temperature
INCs	Incidents of noncompliance
ISO	International Organization for Standardization
IVA	Independent verification agent
LP	low pressure
LSH	level safety high
MAWP	Maximum allowable working pressure
MMS	Minerals Management Service
MOAs	Memoranda of Agreement
MODU	mobile offshore drilling unit
MOU	Memorandum of Understanding
NAE	National Academy of Engineering
NPRM	Notice of Proposed Rulemaking
NTL	Notices to Lessees and Operators
NTTAA	National Technology Transfer and Advancement Act
OESC	Ocean Energy Safety Advisory Committee
OFR	Office of the Federal Register
OIRA	Office of Information and Regulatory Affairs
OMB	Office of Management and Budget
OCS	Outer Continental Shelf
OCSLA	Outer Continental Shelf Lands Act
P&ID	piping and instrumentation diagram

PE	Professional Engineer
PLC	programmable logic controller
PRA	Paperwork Reduction Act
PSH	pressure safety high
PSHL	pressure safety high and low
psi	Pounds per square inch
psia	pounds per square inch absolute
psig	pounds per square inch gauge
PSL	pressure safety low
PSV	pressure safety valve
RFA	Regulatory Flexibility Act
RP	Recommended Practice
SBA	Small Business Administration
SBREFA	Small Business Regulatory Enforcement Fairness Act
SAFD	safety analysis flow diagram
SDV	shutdown valve
Secretary	Secretary of the Interior
SEMS	Safety and Environmental Management Systems
SIL	safety integrity level
SWRI	Southwest Research Institute
Spec.	Specification
SPPE	Safety and Pollution Prevention Equipment
SSSV	Subsurface safety valve
SSV	surface safety valve
TLPs	tension-leg platforms
TSE	temperature safety element
TSH	temperature safety high
USCG	U.S. Coast Guard
USV	Underwater safety valve
VRU	vapor recovery unit
WI	water injection
WISDV	water injection shutdown valve
WIV	water injection valve